

FIXED VOLTAGE POWER SUPPLY

SPS-9620

High Current Switching Mode DC Regulated Power Supply

Manson®



Description

The SPS-9620 DC power supply has been designed for professional applications which require quality high current for equipments such as super power car audio that are normally operated from twelve volt batteries.

The output is current limited at just over 120A and this current output can be supplied continuously.

The output voltage has Over Voltage Protection at about 17V to ensure very high protection against power supply failure, thus offering full protection to the powered equipment .

The excellent load regulation is further enhanced with remote sensing terminals to give precise voltage at the point of application for long connecting leads.

The output voltage range can be easily fine tuned between 12.6V to 14.3V via a concealed trimmer. This covers most 12V battery sources such as six lead-acid cells (13.8V) or ten nickel-cadmium cells (12.6V) and etc.

The excellent Dynamic Power Factor Correction (>0.9) reduces unnecessary power loss (cuts electricity cost in some countries) and cuts the noise and EMI to your power mains.

Features

- Output Over Voltage Protection at 16.5V Trimmer fine tune output voltage 12.6 to 14.3 V for 13.8 V nominal .
- Constant Current Limiting Over Load Protection Short circuit and Over temperature Protection.
- Green LED for power on/off indication
- Red LED for overload / short circuit protection
- Excellent line and load regulation.
- Remote sensing terminal for precise voltage load with long leads.
- Low ripple and noise
- Cooling fan is on all the time, speed of fan increase with temperature of unit.
- High efficiency 85%
- CE Approval : EMC: EN55022 LVD: EN 60950
- Light weight and Compact: 11Kg., 23Wx22Hx34D cm
- High RFI Stability
- Floating Ground

Specifications

Models	SPS-9620
Output Voltage	Fixed 13.8VDC (Fine tune 12.6 - 14.3VDC)
Rated Output Current	120A
Ripple & Noise (peak-peak)	≤50mV
Load Regulation with Sense (0-100% load)	0.1% +5mV
Load Regulation with no Sense (0-100% load)	0.1% +5mV
Line Regulation (190-254VAC variation)	0.05% +3mV
Input Voltage	200-240VAC 50Hz~ (or on request)
Efficiency	≥85%
Dynamic Power Factory Correction	>0.97 at optimal load
Indicator	Green LED: Power ON/OFF Red LED: Overload/Short Circuit
Special Feature	Remote Sensing
Cooling System	Variable speed thermally static control fan (from 1/3 to full speed)
Operating Temperature	0 - 40°C
Protection Devices	Overload (Constant Current Limiting), Over Temp., Short Circuit, OVP
Approvals	CE EMC: EN 55022 LVD: EN 60950
Dimensions (WxHxD)	235x218x345 mm 9.6x8.6x13.6 inch
Weight	11 kgs 24 lbs

■ All values are based on the Standard ambient Temperature 25°C and Pressure 0.1Mpa.

■ SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE