



J2
CH A

1 TEMP SENSOR POWER
2 TEMP SENSOR OUTPUT
3 GROUND
4 CLIP A-
5 CLIP A+
6 SPKR LEVEL A
7 GROUND

J1
DISPLAY

1 GROUND
2 CLIP B+
3 SPKR LEVEL B
4 CLIP B-
5 MUTE B
6 +20 V
7 MUTE A
8 CLIP A-
9 SPKR LEVEL A
10 CLIP A+
11 GROUND
12 GROUND
13 GROUND

J3
CH B

1 TEMP SENSOR POWER
2 TEMP SENSOR OUTPUT
3 GROUND
4 CLIP B-
5 CLIP B+
6 SPKR LEVEL B
7 GROUND

J5
FAN

1 DRIVE V+
2 GROUND

J6
VU DSP

1 V+
2 GROUND
3 SIGNAL B
4 SIGNAL A

NOTE 1 C2 - C7 ARE 6,800uF/90V ON MODEL FA1201
C2 - C5 ARE 7,300uF/80V ON MODEL FA901. C6, C7 ARE NOT USED
C2 & C4 ARE 10,000uF/67V ON MODEL FA601. C3, C5, C6, C7 ARE NOT USED

NOTE 2 R7 & R8 ARE 1K/1% ON MODELS FA901 & FA1201, AND 750/1% ON MODEL FA601

CREST AUDIO INC.
150 Florence Ave.
Hawthorne, NJ 07506
Title FA SERIES POWER SUPPLY/FAN DRIVER
Size C Document Number 21C0998 Rev 2
Date: Thursday, May 18, 2000 Sheet 1 of 1