



NOTES:

UNLESS OTHERWISE SPECIFIED,

1. ALL RESISTORS ARE EXPRESSED IN OHMS AND ARE 1/4W, 5%.
2. ALL CAPACITORS ARE EXPRESSED IN MICROFARADS.
3. ALL S2L AND NPO CERAMIC DISC CAPACITORS ARE +/-5%.
4. ALL Y5E CERAMIC DISC CAPACITORS ARE +/-10%.
5. ALL Z5U CERAMIC DISC CAPACITORS ARE +/-20%.
6. ALL RADIAL ELECTROLYTIC CAPACITORS ARE +/-20%.
7. ALL DIODES ARE 1N4148.
8. ALL SWITCHES ARE SHOWN IN THE "OUT" POSITION.
9. ▽ DENOTES GROUNDS ARE TIED TOGETHER AND RETURN TO CENTRAL GROUND SEPARATELY.
10. +10V DENOTES VOLTAGES ARE TIED TOGETHER AND RETURN TO MAIN SUPPLY SEPARATELY.
11. EXT CV IN IS SCALED AT -50mV/dB.
12. ▢ DENOTES DISTRIBUTION AMP/MIXER JUMPER CONNECTOR, SHOWN IN THE "DISTRIBUTION AMP" POSITION.
13. ▣ DENOTES BALANCED/NON-BALANCED JUMPER CONNECTOR, SHOWN IN THE "BALANCED" POSITION.