



**CAUTION** 500 VOLTS AVAILABLE. DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS MINIMUM FOR BLEEDERS TO DISSIPATE B+ VOLTAGES.

**TEST DATA**  
 (MV) DENOTES TYPICAL 1KH<sub>2</sub> SIGNAL FOR 10 WATTS OUTPUT  
 (A) INSERT BLANK PLUG INTO INPUT JACK FOR THIS TEST.  
 CONTROL SETTINGS- EQUALIZERS AT MID POSITION.  
 PRESENCE AT MINIMUM.  
 OTHERS AT MAXIMUM.

**FENDER MUSICAL INSTRUMENTS**  
 CBS MUSICAL INSTRUMENTS  
 A DIVISION OF CBS INC.  
 FULLERTON CALIFORNIA  
 U.S.A.

- 3. USED IN SOME VERSION.
  - 2. ALL RESISTORS ARE 1/2W, 10%.
  - 1. ALL CAPACITORS AT LEAST 600 V.D.C.
- NOTES: UNLESS OTHERWISE SPECIFIED

**Fender / Rosen / Rhodes**  
ONE ORIGINAL INSTRUMENTS - A DIVISION OF CBS INC. FULLERTON, CALIFORNIA, U.S.A.

**- SCHEMATIC -**  
**180W STUDIO BASS**

FIG. NO. **013606** REV. **A**