



POWER, ON-OFF/  
5 5A  
L2

SHORTS  
ADJUST  
R1  
2 MEG  
D  
R2  
82 M  
E  
S4  
LEAKAGE  
S3  
QUALITY  
G  
H  
LOAD  
5 2A  
R3  
56 K  
M  
C1  
.047  
N  
C  
L1  
NE 2L  
A  
D1  
10 M  
R4  
C2  
.1  
C3  
.1  
R5  
5.6 M  
B  
D4  
R6  
4.7 K  
C4  
160  
40V  
C5  
150  
25V  
R7  
32 K  
R8  
8.2 K  
R9  
8.2 K  
R10  
880 Ω  
R11  
220 Ω  
R12  
220 Ω  
R13  
4 Ω  
R14  
142 Ω  
12 V  
R15  
4.7 K  
R16  
10 K  
R17  
3.3 K  
R18  
470 Ω  
R19  
39 K  
R20  
82 M  
C6  
10 K  
C7  
.047  
C8  
10 K  
C9  
10 K  
C10  
10 K  
C11  
10 K  
C12  
10 K  
S5  
LOCKOUT  
7  
5  
3  
1  
2  
4  
6  
8  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100

2 BOTTOM VIEWS

CIRCLED LETTERS INDICATE  
P.C. BOARD TERMINATION  
POINTS

WHT/RED  
WHT/YEL

488-089-9-001E  
607/667