



CATHODE LEAD WELDED TO CASE.

SILICON RECTIFIER SPECIFICATIONS

1. TYPE : MOTOROLA # 1N4998
2. MECHANICAL: CONSTRUCTION PER THIS DRAWING.
3. ELECTRICAL: ALL STANDARD MOTOROLA 1N4998 SPECIFICATIONS APPLY.
4. MARKING : STAMP LAMBDA PART NO. FBL-047 ON SIDE OF CASE.
5. To protect against damage due to electrostatic discharge, these units must be manufactured, handled and shipped in accordance with DOD STD. 198B.

REVISIONS		
SYM.	DESCRIPTION	APP'D.
A	ORIGINAL	WLB
B	REVISED CATHODE LEAD CONFIG. AND NOTE FROM SOLDERED TO WELDED.	WLB
C	ADDED NOTE 5: PER ECD # A01987	3-2-77
D	CHG. MPR # PER ECD #	1-25-77

USED ON	NEXT ASSY.
DR. WLB	CHK. EWS
MATERIAL:	
FINISH:	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: DEC. 3/16" FRACTIONS 3/64" ANGLES 3/16"	
TITLE: SILICON RECTIFIER	
SCALE: 2:1	
LAMBDA ELECTRONICS CORP.	