



REVISIONS

DOC. NO. SPC-F004 * Effective: 7/8/02 * DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
430	A	RELEASED	JWM	10/4/02	HO	2/11/03	DJC	2/25/03

General Specifications

Display

- 160 x 160 pixel graphic LCD (Viewing area: 63mm x 63mm)
- EL back-light

Measurement Rate

- Digital: 4 times/sec.
- Bar-Graph: 7 times/sec

Auto-Power Off

- 30 minutes
- Set up made (enable/disable)

Over Range Indication

- "OVER" display with beeper sound

Power

- 6 "AA" cells (9V Alkaline) or 6 "A" (7.2V) NiCd battery or 2 rechargeable Ni-Cd battery pack or AC adapter with internal charger
- Operating Time: Alkaline: 6 hrs. approx.
NiCd: 6 hrs. approx.
- Charging Time: 10 hrs approx. (with AC adapter)

Temperature:

- Operating Temp: 0°C ~ 40°C
- Storage Temp: -20% ~ 60°C (NiCd batteries removed)
- Charging Temp: 0°C to 45°C

RS232 Computer Interface

- Baud rate: 1200, 2400, 4800, 9600 bps
- Data bit: 8 bit
- Stop Bit: 1 bit
- Parity: none

Protection Level: (Class II: DC 1000V AC700V)

- per IEC1010-1

Size:

- 107mm(W) x 220mm(L) x 55mm(D)

Weight:

- 800g (net meter only)



Standard Accessories

- Alligator clip set
- Test lead set
- Operator Manual
- Holster Case
- AC power adapter
- RS232 interface cable
- Software PC diskette
- BNC adapter
- Oscilloscope probe

SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jeff McVicker	10/4/02	5Mhz Multifunction Oscilloscope			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	Hisham Odish	2/11/03	A	72-6920	36C3019.dwg	A
APPROVED BY:	DATE:	SCALE:	U.O.M.:	SHEET:		
Daniel Carey	2/25/03	NTS	Millimeters	1 OF 3		

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

Electrical Specifications

Multimeter

DC Voltage (Auto/Manual)

Range	Resolution	Accuracy	Input Impedance	Overload Protection
400mV	0.1mV	±(0.3% rdg +5 digits)	10M	1,000V DC or AC Peak within 10 Seconds
4V	1mV			
40V	10mV			
400V	100mV			
1000V	1V			

AC Voltage (True RMS)

Range	Resolution	Accuracy		
		50Hz ~ 1KHz	1 KHz ~ 10KHz	10KHz ~ 30KHz
400mV	0.1mV	±(1.0% rdg +10 digits)	±(5.0% rdg +10 digits)	ns
4V	1mV	±(0.75% rdg +10 digits)	±(2.0% rdg +10 digits)	±(5.0% rdg +10 digits)
40V	10mV		±(1.0% rdg +10 digits)	
400V	100mV		±(1.0% rdg +10 digits)	
700V	1V	±(1.0% rdg +10 digits)	ns	ns

Resistance

Range	Resolution	Accuracy	Overload Protection
400	0.1	±(0.5% rdg + 10 digits)	250V DC or AC Peak within 10 Seconds
4K	1		
40K	10		
400K	100		
4M	1K		
40M	10K	±(1% rdg +5 digits)	

Diode Test

Range	Resolution	Accuracy	Open Circuit Voltage
Diode	1mV	±(2% rdg +5 digits)	Max. 5.0V

Capacitance

Range	Resolution	Accuracy
40nF	0.01nF	±(2% rdg + 10 digits)
400nF	0.1nF	
4µF	1nF	
40µF	10nF	
100µF	100nF	

Current (DC) Auto/Manual

Range	Resolution	Accuracy	Overload Protection
40mA	10µA	±(1.2% rdg + 10 digits)	250V/500mA Fused
400mA	100µA		
4A	1mA	±(1.5% rdg + 10 digits)	250V / 20A Fused
20A	10mA		

Current (AC) True RMS : Auto/Manual

Range	Resolution	Accuracy		Overload Protection
		50Hz ~ 1KHz	1KHz ~ 10KHz	
40mA	10µA	±(1.2% rdg + 10 digits)	±(4.0% rdg + 10 digits)	250V/500mA Fused
400mA	100µA			
4A	1mA	±(2.0% rdg + 10 digits)		250V / 20A Fused
20A	10mA			

SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	72-6920	36C3019.dwg	A
SCALE: NTS		U.O.M.: Millimeters	SHEET: 2 OF 3

Electrical Specifications

Multimeter (continued)

Continuity

- less than 60Ω, buzzer sounds

AUX

- 400mV full scale DC Adapter required
- Temperature (°C, °F)
- Humidity (%RH)
- Hi current (A)

dB

- Reference Values: 2, 4, 8, 16, 50, 75, 93, 110, 125, 135, 150, 300, 600, 900, 1000, 1200

Video A/D Converter

- Resolution: 8 bits
- Sampling: 20 MS/S

Data Length

- Single Shot: 256 points

Cursor

- Type: ΔV, Δt%, Δt, Δ1/t

Test Probe

- Test Lead with Alligator Clip set
- Scope Probe (1:1) with BNC Adapter

Frequency Counter

- Range: 5Hz ~ 1.3 GHz
- Display: 8 digits
- Period Adjustment: 5Hz ~ 100MHz
- Internal Gate Time: 0.1S, 1S, 10S
- Display Hold Mode
- RPM Display
- Input Measurement:
 - CH A: 5Hz ~ 40MHz
 - CH B: 40MHz ~ 1.3 GHz
- Input Sensitivity:
 - 5Hz~10MHz: 100mV rms
 - 10MHz~40MHz: 200mV rms
 - 40MHz~80MHz: 300mV rms
 - 80MHz~1.3GHz: 200mV rms
- MIN/MAX/AVG:
 - Records minimum, average, and maximum
 - History graph display
- Hold: captures current reading
- Peak Hold:
 - Records peak maximum, minimum
 - History graph display

Digital Storage Oscilloscope (DSO)

Read Out Type

- Rising Time: less than 15nS
- Input Impedance: 1 Megohm
- Autosetting

Vertical

- Number of Channels: One
- Sensitivity: 10mV/div ~ 200V/div (14 divisions)
- Bandwidth: DC to 5MHz
- Sample Rate: 25MS/s
- Input Protection: 600Vpp

Horizontal

- Sweep: 125ns ~ 2s/div (23 divisions)
- Sweep Mode: Auto

Trigger

- Auto, Manual
- Slope: Rising, falling
- Trigger Adjustable: 15% ~ 85%

Input Impedance

- CH A: 1Megohm
- CH B: 50Megohm

Maximum Input Voltage

- CH A: 100V p/p
- CH B: 5V p/p

Simultaneous display in one screen (frequency, period, rpm)

Function Generator

- Output: Sine, triangle, square wave
- Range: 40Hz ~ 5MHz (6 range)
- Display: 3 digits
- Output Impedance: 600 ohm
- Amplitude: 2V~10V p/p
- Duty Cycle: 25%~75%
- Simultaneous display in one screen (frequency, period, duty, amplitude)

Logic Analyzer

Vertical

- Input Channel: one
- Input Impedance: 1 megohm
- Protection Level: 50V p/p max.

Horizontal

- Sweep Time: 125ns~2s/div (23 divisions)
- Sweep Mode: auto

SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	72-6920	36C3019.dwg	A
SCALE:	NTS	U.O.M.: Millimeters	SHEET: 3 OF 3